



PUREWATER



OzoneGenerator

Prozone advanced hybrid Ozone Generator

- PZ6-V — Venturi driven and provides waterline sanitation
- Prozone has made purification safe and cost-effective
- Highly efficient using solid-state drivers with EMI
- Surge suppression to ensure bath controls are not affected
- Thermally protected
- PZ6-CT — Compressor driven, controlled by automated timer, airline sanitation



BALBOA
water group

OzoneGenerator

INSTALLATION NOTES

- The PZ6 - V connects to the whirlpool piping and the ozone is drawn into the water by a venturi. This allows the ozone to mix with the water so that water can be sanitized while the pump is running.
- The PZ6 - CT has an integral timer that activates the generator and compressor for 15 minutes every 6 hours. This helps ensure that the ozone permeates the whirlpool system to sanitize the lines between uses of the whirlpool.
- The installation kit includes a check valve, clamps, tubing, 1' x 1' x 1" schedule 40 PVC tees, 1" x 1/2" reducer fittings, 1/4" HB Wye fitting and 1/4" HB x 1/2" slip fittings.

ITEM NO.	PART NO.	DESCRIPTION
1	1713001	Ozone Generator with Compressor & Timer (PZ6-CT)
2	1713003	Direct Injection Installation Kit for Whirlpool Bathtubs
3	1713004	Ozone Generator without Compressor or Timer (PZ6-V)

SPECIFICATIONS

110 VAC, 60hz	35 amps
Ozone Output	4,000 mg/day
Ozone Purity	99.9% Hydroxyl Free, 100% Free of Nitrous Compounds
Size	6.25" x 6.25" x 2.5"
Case	High Impact Polymer
Ozone Concentration 1CFH	600 PPM
System Life	20,000 hours (nominal)
Operating Temperature	+25°F. to +140°F.
Weight	14 ounces
Motor Pad	316 Stainless Steel
EMI Suppression and Transient Protected	Up to 2,000 VAC

